

TECHNICAL DATA

Technical Specifications Strava Splint Bath

Strava SPLINT BATH	UM	Spec
Operating Temperature Range	F	140° - 180° F
	C	60° - 82° C
Sanitation Mode	F	185°
	C	85°
Temperature Variability	F/C	2°
Set Time	Seconds	30 - 180
Over Voltage	W	11
Frequency	Hz	50/60 Hz
Mains Voltage (+/- 10% of nominal voltage)	V	100-120 VAC, 200-240 VAC
Power Consumption	W	1100W
AC Current (Max)	A	<10 Amps
Water Fill Capacity	Gallons	5.2 G
	Litres	20 L
Water Fill Height	in	5"
	cm	12.5 cm
Unit Weight	lbs	35 lbs
	kg	15.9 kg
Unit Dims Outer (LxWxH)	in	22.625"L 19.75"W 10"H
	cm	60cm L 52cm W 25.5cm H
Unit Dims Inner (LxWxH)	in	19"L 12"W 6"H
	cm	48cm L 30cm W 15cm H
Unit Shipping Weight	lbs	47 lbs
	kg	21 kg
Unit Shipping Dims (LxWxH)	in	26.5"L 23"W 16"H
	cm	67cm L 59cm W 41cm H
Standard		IEC 61010-1, -2
		UL 61010-1, -2
		CSA C22.2#61010-1, -2
		CB SCHEME
Environment (Altitude)		
	Operation (Max)	
	ft	16,732 ft
	m	5100 m
Storage (Altitude)		
	ft	16,732 ft
	m	5100 m